


**TRIANGULAR DEPRESSION  
FOR PREVAILING TORQUE  
SHAPE AS SHOWN**



**GRADE A - ZINC PLATED \***

" A " COARSE THREAD		" A " FINE THREAD		" B " WIDTH ACROSS FLATS		" C " THICKNESS	
SIZE	PART NO.	SIZE	PART NO.	MAX.	MIN.	MAX.	MIN.
10-24	FH1024TAZ	10-32	FH1032TAZ	.375	.362	.203	.187
1/4-20	FH1420TAZ	1/4-28	FH1428TAZ	.438	.428	.226	.212
5/16-18	FH51618TAZ	5/16-24	FH51624TAZ	.500	.489	.273	.258
3/8-16	FH3816TAZ	3/8-24	FH3824TAZ	.562	.551	.337	.320
7/16-14	FH71614TAZ	7/16-20	FH71620TAZ	.688	.675	.385	.365
1/2-13	FH1213TAZ	1/2-20	FH1220TAZ	.750	.736	.448	.427
9/16-12	FH91612TAZ	9/16-18	FH91618TAZ	.875	.861	.496	.473
5/8-11	FH5811TAZ	5/8-18	FH5818TAZ	.938	.922	.559	.535
3/4-10	FH3410TAZ	3/4-16	FH3416TAZ	1.125	1.088	.665	.617
7/8-9	FH789TAZ	7/8-14	FH7814TAZ	1.312	1.269	.776	.724
1-8	FH18TAZ	1-14	FH114TAZ	1.500	1.450	.887	.831

**NOTES:**

- 1 - MECHANICAL AND PERFORMANCE REQUIREMENTS PER IFI 100/107
- 2 - ALSO AVAILABLE IN GRADE "B" AND "C".

**\* COMMON FINISHES LISTED - OTHER FINISHES AVAILABLE**

**FINISHED HEX NUT**  
**TOP LOCK**  
**GRADE A**



SCALE	UNITS	DWG TYPE	REV
NONE	INCH	S	NONE